

Find it at



PRECISION
FLUID POWER, INC.
Hydraulic Sales & Repair
800-728-5168 PrecisionFluidPower.com

MODEL CODES

EDITION III



Linde Hydraulics Corporation

5089 West Western Reserve Road

Canfield, Ohio 44406

Telephone: (330) 533-6801

Fax: (330) 533-2091

Model Codes for H-Series-02 Closed Loop Pumps

MODEL	1 DISPLACEMENT (cc/rev)	2 ROTATION	3 CONTROL	4 CONTROL OPTIONS	5 MOUNTING	6 SHAFT	7 R/V SETTING	8 DISP. MAX.	9 DISP. MIN.	10 ADD-ONS	11 SPECIALS
HPV											
EXAMPLE:	105	R	K	1	C	H	420	X	X	AX	X

1 DISPLACEMENT
75 (4.63 cir)
105 (6.41 cir)
135 (8.27 cir)

2 ROTATION
R = CLOCKWISE
L = COUNTER-CLOCKWISE

3 CONTROL
H = HYDRAULIC REMOTE
E = PROPORTIONAL ELECTRIC
K = MANUAL CAM LEVER

4 CONTROL OPTIONS
HPV 'K' 1 = KORIF 1.0
 2 = KORIF 0.7
 3 = KORIF 0.8
 4 = KORIF 1.2
 5 = KORIF 1.5
E CONTROL 1 = 12 VDC
 2 = 24 VDC

5 MOUNTING
C = SAE C 2 BOLT MTG (75, 105)
D = SAE D 2 BOLT MTG (135)

6 SHAFT
H = ANSI 21T 16/32 P (75)
 23T 16/32 P (105)
 27T 16/32 P (135)
C = SAE C 14T 12/24 P
 (OPT 75, 105)
D = SAE D 13T 8/16 P (OPT 135)

7 RELIEF SETTING
IN BAR

**8 MAX. DISPLACEMENT
(SINGLE UNITS ONLY)**
IF NOT DESTROKED, ENTER "X".
OTHERWISE, SPECIFY SETTING
IN CC/REV.

**9 MIN. DISPLACEMENT
(SINGLE UNITS ONLY)**
ENTER "X", FOR ZERO MIN.
DISPLACEMENT. OTHERWISE,
SPECIFY SETTING IN CC/REV.

10 ADD-ONS
PTO'S:
A = SAE A w/9T SPLINE
 COUPLING (std. on all
 Models)
B = SAE B w/13T SPLINE
 COUPLING (2)
J = SAE B w/15T SPLINE
 COUPLING (2)
C = SAE C w/14T SPLINE
 COUPLING (2)
ADDITIONAL CONTROLS OPTIONS:
P = PRESSURE OVERRIDE
X = NONE
Z = ZERO FLOW DEVICE (1)

11 SPECIALS
INSERT S, THEN CALL OUT
REQUIREMENT IN CLEAR TEXT.

NOTES: (1) Only available with "E" Control Option.
(2) PTO Option removal of Integral Boost Pump and necessities provision for external supply.